

Inner Door Escutcheons | Wall Mounted

Inner door escutcheons enable operators to access control equipment while maintaining separation of hazardous voltage equipment. Inner door kits can be fitted to all IP Enclosures wall mounted electrical enclosures without drilling.

STEEL RANGE

Material: 1.2-1.5mm galvanised steel sheet

Lock: Chrome 5mm double bit insert quarter turn lock.

Surface Treatment: UL approved epoxy polyester powder coated with a textured finish. 80-120 micron average thickness.

Standard colour: RAL7035. Other colour options are available. Refer to table below.



STEEL



Size H x W (mm)	Accessories Inner Door	Clearance Dimensions Inner Door to Outer Door	Clearance Dimensions Inner Door to Mounting Plate: Enclosure Depth					Part Number Suffix Optional Colours
			150mm	200mm	250mm	300mm	400mm	
300 x 200	IP-PSID3020	68.3mm	67.8mm	-	-	-	-	-T33 -BLK -OR -RED
300 x 300	IP-PSID3030	68.3mm	67.8mm	117.8mm	-	-	-	-T33 -BLK -OR -RED
400 x 300	IP-PSID4030	68.3mm	-	117.8mm	-	217.8mm	-	-T33 -BLK -OR -RED
400 x 400	IP-PSID4040	68.3mm	-	117.8mm	-	217.8mm	-	-T33 -BLK -OR -RED
500 x 300	IP-PSID5030	68.3mm	67.8mm	117.8mm	-	-	-	-T33 -BLK -OR -RED
500 x 400	IP-PSID5040	68.3mm	-	117.8mm	167.8mm	-	-	-T33 -BLK -OR -RED
500 x 500	IP-PSID5050	68.3mm	-	117.8mm	167.8mm	217.8mm	-	-T33 -BLK -OR -RED
600 x 400	IP-PSID6040	68.3mm	-	117.8mm	167.8mm	217.8mm	-	-T33 -BLK -OR -RED
600 x 600	IP-PSID6060	68.3mm	-	117.8mm	-	217.8mm	317.8mm	-T33 -BLK -OR -RED
700 x 500	IP-PSID7050	68.3mm	-	117.8mm	167.8mm	-	-	-T33 -BLK -OR -RED
800 x 600	IP-PSID8060	68.3mm	-	117.8mm	167.8mm	217.8mm	-	-T33 -BLK -OR -RED
800 x 800	IP-PSID8080	68.3mm	-	117.8mm	-	217.8mm	317.8mm	-T33 -BLK -OR -RED
1000 x 600	IP-PSID10060	68.3mm	-	-	167.8mm	217.8mm	-	-T33 -BLK -OR -RED
1000 x 800	IP-PSID10080	68.3mm	-	117.8mm	-	217.8mm	317.8mm	-T33 -BLK -OR -RED
1000 x 1000	IP-PSID100100	68.3mm	-	-	-	217.8mm	317.8mm	-T33 -BLK -OR -RED
1200 x 600	IP-PSID12060	68.3mm	-	-	-	217.8mm	-	-T33 -BLK -OR -RED
1200 x 800	IP-PSID12080	68.3mm	-	-	-	217.8mm	317.8mm	-T33 -BLK -OR -RED
1200 x 1000	IP-PSID120100	68.3mm	-	-	-	217.8mm	317.8mm	-T33 -BLK -OR -RED
1200 x 1200	IP-PSID120120	68.3mm	-	-	-	217.8mm	317.8mm	-T33 -BLK -OR -RED

STAINLESS STEEL RANGE

Material: 1.2-1.5mm Grade 316/316L Stainless Steel

Lock: 316 Stainless Steel 8mm square drive quarter turn lock.

STAINLESS STEEL

Size H x W (mm)	Accessories Inner Door	Clearance Dimensions Inner Door to Outer Door	Clearance Dimensions Inner Door to Mounting Plate: Enclosure Depth				
			150mm	200mm	250mm	300mm	400mm
300 x 200	IP-SSID3020	68mm	67.2mm	-	-	-	-
300 x 300	IP-SSID3030	68mm	67.2mm	117.2mm	-	-	-
400 x 300	IP-SSID4030	68mm	67.2mm	117.2mm	-	-	-
400 x 400	IP-SSID4040	68mm	-	117.2mm	-	-	-
500 x 400	IP-SSID5040	68mm	-	-	167.2mm	-	-
500 x 500	IP-SSID5050	68mm	-	117.2mm	167.2mm	-	-
600 x 400	IP-SSID6040	68mm	-	117.2mm	-	217.2mm	317.2mm
600 x 600	IP-SSID6060	68mm	-	117.2mm	-	217.2mm	317.2mm
700 x 500	IP-SSID7050	68mm	-	-	167.2mm	-	-
800 x 600	IP-SSID8060	68mm	-	-	167.2mm	217.2mm	-
800 x 800	IP-SSID8080	68mm	-	-	-	217.2mm	-
1000 x 600	IP-SSID10060	68mm	-	-	-	217.2mm	-
1000 x 800	IP-SSID10080	68mm	-	-	-	217.2mm	317.2mm
1000 x 1000	IP-SSID100100	68mm	-	-	-	217.2mm	317.2mm
1200 x 800	IP-SSID12080	68mm	-	-	-	217.2mm	-
1200 x 1000	IP-SSID120100	68mm	-	-	-	217.2mm	317.2mm
1200 x 1200	IP-SSID120120	68mm	-	-	-	217.2mm	317.2mm

